

Adsorption Studies on the Removal of Hexavalent Chromium-Contaminated Wastewater Using Activated Carbon and Bentonite

SALAH ABDEL WANEES¹, ABDEL MONEM M. AHMED^{2,*}, MOHAMED S. ADAM³ and MAMDOUH A. MOHAMED^{1,*}

¹Department of Chemistry, Faculty of Science, Zagazig University, Zagazig City 44519, Sharkia Province, Egypt ²Department of Chemistry, Faculty of Science, Alexandria University, Alexandria, Egypt ³Department of Chemistry, Faculty of Science, Sohag University, Sohag, Egypt

*Corresponding authors: Tel./Fax: +20 93 2303929; E-mail: mamsahar2020@yahoo.com; profabdelmonem@gmail.com

(Received:	11	October	2012;
------------	----	---------	-------

Accepted: 16 August 2013)

AJC-13925

In this study, the adsorption potential of activated carbon and bentonite for removal of Cr(VI) ions from wastewater has been investigated. The study involves batch type experiments to investigate the effect of initial concentration, adsorbent dose, agitation speed, contact time, temperature and pH of solution on adsorption process and the optimum conditions were evaluated. The adsorption process has fit pseudosecond order kinetic models. Langmuir and Freundlich adsorption isotherm models were applied to analyze adsorption data and both were found to be applicable to this adsorption process. Thermodynamic parameters, *e.g.*, ΔG° , ΔS° and ΔH° of the on-going adsorption process have also been calculated and the sorption process was found to be endothermic. Finally, it can be seen that bentonite was found to be more effective for the removal of Cr(VI) than activated carbon, under the same experimental conditions.

Key Words: Wastewater, Chromium, Activated carbon, Bentonite, Removal.

INTRODUCTION

The pollution of heavy metal ions in the environment is a critical problem because of their toxicity and other adverse effects on the receiving waters and/or soils. They must be removed from wastewater before discharging them into water bodies. Water pollution by chromium is due to both, natural sources and man made activities. Chromium is found in rocks, animals, plants, soils and in volcanic dusts and gases. Various industrial processes such as steel production, electroplating, leather tanning, nuclear power plants, textile industries, wood preservation, anodizing of aluminum, water-cooling and chromate preparation¹. Discharge chromium containing wastes with varied concentration between 5 and 220 mg/L into the environment, which contaminates soil and water^{2,3}. The world mine production of chromite was estimated at a gross mass of 13×10^6 metric tons in 2002⁴. In nature chromium exists in two most stable oxidation states, *i.e.*, trivalent and hexavalent forms in aqueous systems. Although, at trace level, the trivalent form is considered as an essential nutrient^{5,6}, hexavalent form of chromium is toxic, carcinogenic and mutagenic in nature⁷⁻¹². The hexavalent form is about 500 times more toxic than trivalent form¹³. Furthermore, Cr(VI) is highly mobile in soil and aquatic system and also is a strong oxidant capable of being adsorbed by skin¹⁴. Considering its toxicity and carcinogenic nature, the maximum levels permitted for trivalent chromium in wastewater 5 mg/L and for hexavalent chromium are $0.05 \text{ mg/L}^{15,16}$.

The most common methods of removal of Cr(VI) ions from aqueous system are chemical precipitation, ion exchange, membrane processes, electrodialysis and adsorption¹⁷⁻²⁰. Hexavalent chromium usually exists in wastewater as oxyanions such as chromate $CrO_4^{2^-}$ and dichromate $Cr_2O_7^{2^-}$ and does not precipitate easily using conventional precipitation methods. Ion exchange, reverse osmosis and elctrodialysis are efficient for Cr(VI) ions removal but the cost is relatively high²⁰. Furthermore, chromium removal techniques such as co-precipitation, membrane techniques and solvent extraction are challenged by the removal of lower concentrations of metals from solution²¹. On the other hand, adsorption has been proved to be one of the respective methods, which is simple, selective and economical process for the removal of heavy metal ions from aqueous solution.

In this work two different adsorbents (activated carbon and bentonite) were used for the removal of hexavalent chromium (Cr^{6+}) from wastewater. Bentonite is considered by many authors as main candidate in the decontamination and treatment of detrimental metal ions, because of its large specific surface area and high adsorption capacity²²⁻²⁴.

	TABLE-1					
SURFACE AREA AND PARTICLE SIZE ANALYSIS OF ACTIVATED CARBON AND BENTONITE						
Adsorbents analysis	Activated carbo	n	Bentonite			
Surface area (BET) Nova 2000 Quantachrome	931.9 m²/g		119.8 m ² /g (dry)			
	Size (micrometer)	Wt. (%)	Size (micrometer)	Wt. (%)		
Particle size (XRD) Philips PW 1730	32-16	2.75	> 63	1		
	16-8	55.89	63-32	1		
	8-4	16.03	32-16	2		
	4-2	21.14	16-8	3		
	< 2	4.19	8-4	2		
			4-2	4		
			< 2	87		

The objectives of the present study are: (1) to study the effect of contact time of Cr^{6+} metal ions adsorption on activated carbon and bentonite; (2) to investigate the influence of pH on the adsorption of Cr^{6+} ; (3) to study the adsorption of Cr^{6+} at different temperatures and to calculate the adsorption thermodynamic parameters (*i.e.*, ΔH° , ΔS° and ΔG°); (4) to find the effect of adsorbent dose and initial concentration on the adsorption isotherms through Langmuir and Freundlich models; (6) to investigate the adsorption properties of Cr^{6+} and to discuss its adsorption mechanism.

EXPERIMENTAL

All chemicals used in this present work were either of analytical reagent or laboratory reagent grade and were used as received. Potassium dichromate (99 %), H_2SO_4 (98 % w/w) supplied by BDH chemicals Ltd. Distilled water was used in all preparations. Potassium dichromate and deionized water were used to prepare synthetic chromium containing wastewater. Powder activated carbon (PAC) produced from natural origin by ADWIC was used as adsorbent as well as American Wyoming calcium bentonite used in Alexandria Company for Refractories.

Powder activated carbon (PAC) and bentonite (clay) were supplied from ADWIC and Alexandria Company for Refractories, respectively. The surface area and particle size analyses for the two adsorbents were checked (Table-1). Elemental analysis for bentonite was evaluated using X-ray fluorescence (Philips PW 1390) as shown in (Table-2).

TABLE-2							
ELEMENTAL ANALYSIS FOR BENTONITE WAS EVALUATED							
USING X-I	USING X-RAY FLUORESCENCE (PHILIPS PW 1390)						
Oxides (wt. %)	Bentonite	Oxides (wt. %)	Bentonite				
SiO ₂ (%)	55.89	Na ₂ O (%)	0.34				
$A1 \cap (0/)$	16.02	TO(0)	0.15				

$SIO_2(n)$	55.69	$1 a_2 O(n)$	0.54
$Al_2O_3(\%)$	16.03	TiO ₂ (%)	0.15
$Fe_2O_3(\%)$	4.19	$P_2O_5(\%)$	0.086
CaO (%)	3.25	SO ₃ (%)	0.23
MgO (%)	2.75	LOI (%)	17.2
$K_2O(\%)$	0.49	-	-

Magnetic hot plate stirrer was used to stir the heavy metal ions solutions with adsorbents (activated carbon or bentonite). A definite volume of heavy metal ions solution with a known initial ions concentration was stirred with a definite amount of adsorbent for certain time at fixed temperature and agitation rate. The pH values of the solutions were measured by digital pH meter (Model μ pH system-361, India). The metal ion concentration was measured using atomic-absorption spectrophotometer, AAS, (Model, AA55; Varian Inc., USA).

Experimental procedures: Potassium dichromate and redistilled water were used to prepare a stock solution with a concentration of 1000 ppm Cr(VI) which was diluted for preparation of test solutions. Several solutions with different initial concentrations of potassium dichromate (50, 100, 200, 300 and 400 ppm) were prepared. The required pH was adjusted by drop wise addition of $0.1 \text{ N H}_2\text{SO}_4$ depending on the acidity of the sample. All experiments were carried out at 25 °C by adding different amounts of adsorbents (0.1, 0.3, 0.5, 0.7 and 1.0 g) to different concentrations of 250 mL of heavy metal ions solution. The agitation rate for all experiments was 200 rpm and the residence time was (0, 15, 30, 45, 60, 75, 90 and 120 min).

1 mL of sample was taken from reaction solution and diluted to 10 mL by redistilled water, adsorbents were then separated from the solution by using filter paper (Whatman No. 40) and the residual Cr^{6+} ions concentration in the solution was then determined by atomic-absorption spectro-photometer.

The effects of several parameters, such as contact time, initial concentration, adsorbent dose, pH and temperature on the adsorption of Cr(VI) ions onto activated carbon and bentonite were studied.

Data analysis: The uptake of Cr(VI) ions was calculated from the mass balance, which was stated as the amount of solute adsorbed onto the solid. It equals the amount of solute removed from the solution. Mathematically, it can be expressed by eqn. 1:

$$q_e = \frac{(C_i - C_e)}{S} \tag{1}$$

where: q_e the heavy metal ions concentration adsorbed by an adsorbent at equilibrium (mg of metal ions/g of adsorbent). C_i is the initial concentration of metal ions in the solution (mg/L). C_e is the equilibrium concentration or final concentration of metal ions in the solution (mg/L). S the dosage concentration and it is expressed by eqn. 2:

$$=\frac{m}{V}$$
 (2)

where V is the initial volume of metal ions solution used (L) and m is the weight of dried used adsorbent (g).

S

The percentage of adsorption (%) is calculated using eqn. 3:

Adsorption (%) =
$$\left[\frac{(C_i - C_e)}{C_i}\right] \times 100$$
 (3)

RESULTS AND DISCUSSION

Effect of contact time: The effect of contact time on Cr(VI) adsorption on both activated carbon and bentonite was investigated to study the rate of Cr(VI) ions removal (Fig. 1). It is easily seen from Fig. 1 that the percentage removal of Cr(VI) metal ions increased with increasing the contact time. The % removal was 73 % for activated carbon and 77 % for bentonite after 120 min. It is clear that, at the beginning % removal increased rapidly in few minutes, by increasing contact time, % removal increased lightly and slowly till reach maximum value and this can be explained on the basis that, initially a large number of vacant surface sites may be available for adsorption of metal ions and by time the surface sites become exhausted²⁵. These results indicate that the activated carbon and bentonite have a strong capacity for adsorption of Cr(VI) ions in solutions.



Fig. 1. Effect of contact time on Cr⁶⁺ ions removal (conditions; adsorbate initial concentration: 400 mg/L; pH: 2; adsorbents dose: 4 g/L; agitation speed: 200 rpm; temperature: 25 °C)

Effect of adsorbent dose: The percentage adsorption of Cr^{6+} ions onto activated carbon and bentonite was studied at different adsorbent doses (0.4, 1.2, 2.0, 2.8 and 4.0 g/L), keeping pH (2), temperature (25 °C), contact time (120 min) and initial Cr^{6+} ions concentration of (400 mg/L) constant (Fig. 2). The results showed that with increasing in adsorbent dose, the percentage adsorption of Cr^{6+} was increased and the maximum removal was observed with adsorbent dose 4 mg/L for activated carbon and bentonite. Increasing the percentage of adsorption with adsorbent dose may be due to the increase in adsorbent surface area and availability of more adsorption sites^{26,27}. But unit adsorption was decreased with increasing in adsorbent dose (Fig. 3). This may be due to overlapping of adsorption sites as a result of overcrowding of adsorbent particles²⁷.

Effect of initial chromium(VI) ions concentration: The initial heavy metal ions concentration is an important parameter in adsorption since a certain amount of adsorbent can adsorb a certain amount of heavy metal ions. The percentage removal of Cr^{6+} was studied by varying Cr^{6+} concentration from



Fig. 2. Effect of variant activated carbon or bentonite adsorbent dosage (0.4, 1.2, 2.0, 2.8 and 4.0 g/L) on the removal of 400 mg/L Cr⁶⁺ ions from wastewater at contact time: 2 h; temperature: 25 °C; agitation speed: 200 rpm



Fig. 3. Effect of variant activated carbon or bentonite adsorbent dosage (0.4, 1.2, 2.0, 2.8 and 4.0 g/L) on the quantity adsorbed for 400 mg/L Cr⁶⁺ ions from wastewater at contact time: 2 h; temperature: 25 °C; agitation speed: 200 rpm

50 to 300 mg/L with 4 g/L adsorbent dose of activated carbon and bentonite at pH (2), temperature (25 °C) and contact time (2 h) is illustrated in Fig. 4.

Fig. 4 showed that the percentage Cr^{6+} ions adsorption was decreased with increasing in initial concentration. But the actual amount of Cr^{6+} ions adsorbed per unit mass of the adsorbent was increased with increasing in Cr^{6+} ions concentration in the test solution (Fig. 5). According to these results, the initial Cr^{6+} ions concentration plays an important role in the adsorption capacities. Higher concentrations of metal ions were used to study the maximum adsorption capacity of adsorbent^{28,29}.

Effect of pH on the uptake of Cr⁶⁺: The pH of the solution is an important variable which controls the adsorption of the metal ions at the solid-water interface. Hence, the influence



Fig. 4. Effect of initial concentration (namely 50, 100, 200 and 300 mg/L) on removal of Cr⁶⁺ ions (conditions; adsorbents dose: 4 g/L; agitation speed: 200 rpm; temperature: 25 °C)



Fig. 5. Effect of initial concentration (namely 50, 100, 200 and 300 mg/L) on quantity adsorbed of Cr⁶⁺ ions (conditions; adsorbents dose: 4 g/L; agitation speed: 200 rpm; temperature: 25 °C)

of pH on the adsorption of Cr^{6+} ions onto activated carbon and bentonite was examined in the pH range of 1-4. These results were represented in Fig. 6, which showed that the adsorption capacities of Cr^{6+} ions onto both adsorbents increased significantly with decreasing pH value and the maximum removals of Cr^{6+} ions by both adsorbents for contact time (2 h) were carried out at pH (2). The improved removal of chromium(VI) at low pH is probably due to reduction of hexavalent chromium to trivalent chromium ions³⁰, eqn. 4.

$$Cr_2O_7^2 + 14H^+ + 6e^1 \rightarrow 2Cr^{3+} + 7H_2O$$
 (4)

At low pH, there is presence of a large number of H⁺ ions, which in turn neutralize the negatively charged adsorbent surface, thereby reducing hindrance to the diffusion of dichromate ions³¹.

Effect of temperature: Fig. 7 indicates the effect of temperature on the removal efficiency of Cr^{6+} ions from wastewater



Fig. 6. Effect of pH for the adsorption of Cr(VI) ions onto activated carbon and bentonite at 25 °C



Fig. 7. Effect of temperature between 25 and 40 °C for the removal of Cr⁶⁺ ions from wastewater (conditions; adsorbate initial concentration: 400 mg/L; pH: 2.0; adsorbents dose: 4 g/L; agitation speed: 200 rpm; contact time: 2 h)

using activated carbon and bentonite. Four different temperatures were considered in this study (25, 30, 35 and 40 °C). The figure showed that the removal efficiency increased by increasing the temperature, where the maximum adsorption (*ca.* 76 %) is achieved at 40 °C in case of activated carbon. The augmentation of the removal efficiency by stepping up the temperature are due to: Firstly, the higher temperatures activate the metal ions for enhancing adsorption at the coordinating sites of the adsorbent and the metal cations became more faster^{32,33}. Secondly, acceleration of some originally slow step(s) and creation of some new activation sites on the adsorbent surface³⁴. Herein, the phenomenon can be observed in both adsorbents, but activated carbon is affected much higher than in case bentonite Fig. 7.

Adsorption kinetics: Adsorption kinetics describe the solute uptake rate which intern control the residence time and hence the size of adsorption equipment. The experimental results for the adsorption of Cr^{6+} ions onto activated carbon

and bentonite showed rapid initial adsorption rate followed by a slower rate. Initially, the adsorption sites are open and the metal ions interact easily with the sites and hence a higher rate of adsorption is observed. Further, the driving force for adsorption (the concentration difference between the bulk solution and the solid-liquid interface) is higher initially and this leads to a higher adsorption rate. However, after the initial period, slow adsorption may be due to slower diffusion of solute into the interior of the adsorbent. Several adsorption kinetics models have been developed to understand the adsorption kinetics and rate limiting step³⁵⁻³⁸.

The following models have been widely used^{37,38} Largergren pseudo-first order model can expressed by eqns. 5 and 6:

$$\frac{\mathrm{d}q}{\mathrm{d}t} = \mathbf{k}_1(\mathbf{q}_e - \mathbf{q}) \tag{5}$$

$$\ln (q_e - q) = \ln q_e - k_1 t \tag{6}$$

The pseudo-second order model is given by eqns. 7 and 8:

$$\frac{\mathrm{d}q}{\mathrm{d}t} = k_2 (q_e - q)^2 \tag{7}$$

$$\frac{t}{q} = \frac{t}{q_e} + \frac{1}{k_2 q_e^2}$$
(8)

where q and q_e are the amount of Cr⁺⁶ metal adsorbed per unit weight of adsorbent (mg/g) at time t and at equilibrium, respectively and k_1 and k_2 are the adsorption rate constants. The initial adsorption rate (h) is equal to k_1q_e and $k_2q_e^2$ (mg g⁻¹ min⁻¹) for first and second order models, respectively.

The applicability of the above two models can be examined by each linear plot of ln (q_e-q) *vs.* t and (t/q) *vs.* t, respectively and are represented in Figs. 8(a,c) and 8(b,d), respectively. To quantify the applicability of each model, the correlation coefficient, R^2 , was calculated from these plots. The linearity of these plots indicates the applicability of the two models. However, the correlation, R^2 , showed that the pseudo-second order model, fits better the experimental data ($R^2 > 0.990$) than the pseudo-first order model (R^2 in the range of 0.888-0.964).





Fig. 8. Pseudo-first order kinetic plots for the adsorption of Cr⁶⁺ ions onto: (a) activated carbon and (c) bentonite. Pseudo-second order kinetic plots for the adsorption of Cr⁶⁺ ions on: (b) activated carbon and (d) bentonite. Initial concentrations: 50, 100 and 200 ppm; pH: 2.0; adsorbents dose: 4 g/L; agitation speed: 200 rpm; temperature: 25 °C

The kinetic parameters calculated are shown in Table-3. It has been found that the equilibrium sorption capacities

ADSORPTION KINETICS MODEL RATE CONSTANTS FOR ADSORPTION OF Cr ⁶⁺ IONS ONTO								
Activated Carbon and Bentonfie AT VARIOUS CONCENTRATIONS AT 25 °C C_0 $q_e exp.$ Lagergren first-orderPseudo-second-order						er		
Adsorbent (mg/L)	(mg/g)	$K_1 (min^{-1})$	q ₁ (mg/g)	\mathbb{R}^2	$k_2 (g g^{-1} min^{-1})$	$q_2 (mg/g)$	R^2	
Activated 50 carbon 200	50	10.5	2.7×10^{-2}	6.95	0.9276	9.7×10^{-3}	10.7	0.9954
	17.25	2.6×10^{-2}	15.0	0.9840	1.9×10^{-3}	20.4	0.9934	
	29.25	2.3×10^{-2}	27.7	0.9371	7.2×10^{-4}	36.9	0.9597	
	50	10.0	2.8×10^{-2}	5.6	0.8851	1.1×10^{-2}	10.5	0.9968
Bentonite 100 200	100	18.0	2.7×10^{-2}	13.2	0.9585	3.0×10^{-3}	18.9	0.9934
	200	31.75	2.5×10^{-2}	24.5	0.9642	1.4×10^{-3}	35.7	0.9912

TADIE 2

determined using second-order model were in agreement with the experimentally determined equilibrium sorption capacities. Also, the rate constant decreased with the solution concentration increasing.

In general, the adsorption reaction is known to proceed through the following three steps: (1) transfer of adsorbate from bulk solution to adsorbent surface, which is usually mentioned as diffusion, (2) migration of adsorbate into pores and (3) interaction of adsorbate with available sites on the interior surface of pores.

Adsorption isotherms: Several models have been used in the literature to describe the experimental data of adsorption isotherm. The Langmuir and Freundlich models are the most frequently employed to describe equilibrium³⁹. The Langmuir isotherm is based on the theoretical principle that only a single adsorption layer exists on an adsorbent and it represents the equilibrium distribution of metal ions between the solid and liquid phases. The basic assumption of the Langmuir adsorption process is the formation of a monolayer of adsorbate on the outer surface of the adsorbent and after that no further adsorption takes place. The Langmuir-type isotherm remains to be the most widely used for practical application. The Langmuir isotherm for pure component adsorption can be obtained from eqn. 9:

$$\frac{C_e}{q_e} = \frac{1}{(q_{max}b)} + \left(\frac{1}{q_{max}}\right)C_e \tag{9}$$

where q_{max} is the maximum metal ions uptake per unit mass of adsorbent (mg/g), which is related to the adsorption capacity and b is Langmuir constant (L/mol) which is exponentially proportional to the heat of adsorption and related to the adsorption intensity. Therefore, a plot of C_e/q_e versus C_e gives a straight line of the slop 1/q_{max} and intercept 1/(q_{max} b) as shown in Fig. 9.

Zeldowitsch³⁹, assuming an exponentially decaying function of site density with respect to heat of adsorption and obtained the classical empirical isotherm (eqn. 10):

$$\ln q_e = \ln K_f + \frac{1}{n} \ln C_e \tag{10}$$

This is known as Freundlich isotherm. The Freundlich adsorption isotherm is an indicator of the extent of heterogeneity of the adsorbent surface, where the Freundlich constants K_f and n, which respectively indicating the adsorption capacity and the adsorption intensity, were calculated from the intercept and slope of the plot of $\ln q_e$ versus $\ln C_e$ as shown in Fig. 10.



Fig. 9. Langmuir adsorption isotherm for Cr⁶⁺ ions adsorption by activated carbon and bentonite at constant temperature 25 °C and contact time 2 h



Fig. 10. Freundlich adsorption isotherm for $\rm Cr^{6+}$ ions adsorption by activated carbon and bentonite at constant temperature 25 $^{o}\rm C$ and contact time 2 h

This Freundlich type behaviour is indicative of surface heterogeneity of the adsorbents, *i.e.*, the adsorptive sites (surface of activated carbon and bentonite) are made up of small heterogeneous adsorption patches that are homogeneous in themselves. The activation of adsorption sites takes place, leading to increased adsorption probably through the surface exchange mechanism. The calculated results of Langmuir and Freundlich isotherm constants are given in Table-4. It can be seen that the Freundlich model yields a much better fit than the Langmuir model, when the R^2 values are compared in Table-4. This suggests that the boundary layer thickness is increased. The Freundlich constant K_f indicates the sorption capacity of the sorbent. From Table-4, the values of K_f are 1.84 and 1.58 for activated carbon and bentonite, respectively.

Furthermore, the value of n is 2.26 and 1.78 for activated carbon and bentonite, respectively. It is noted that the values of n are bigger than 1, reflecting the favorable adsorption. On the other hand, the q_{max} and the adsorption intensity values of bentonite are higher than activated carbon. The calculated b values indicate the interaction forces between bentonite surface and Cr⁶⁺ ions are stronger than in case of activated carbon, this means that the bentonite is more powerful adsorbent than activated carbon. These results indicate that both adsorbents have a very strong adsorption capacity towards Cr⁶⁺ ions.

Thermodynamic parameters: Thermodynamic parameters such as free energy (ΔG°), enthalpy (ΔH°) and entropy (ΔS°) changes of adsorption can be evaluated from the following equations (11,12):

$$K_{c} = \frac{A_{Ae}}{C_{e}}$$
(11)

$$\Delta G^{o} = - RT \ln K_{c}$$
 (12)

where K_c is the equilibrium constant and C_{Ae} and C_e (both in mg/L) are the equilibrium concentrations for solute on the sorbent and in the solution, respectively. The K_c values are used in eqns. 11 and 12 to determine the ΔG^o , ΔH^o and ΔS^o , the K_c may be expressed in terms of the ΔH^o (kj mol⁻¹) and ΔS^o (kj mol⁻¹ K⁻¹) as a function of temperature, eqn. 13:

$$\ln K_{c} = -\frac{\Delta H^{o}}{RT} + \frac{\Delta S^{o}}{R}$$
(13)

Thermodynamic parameters such as free energy of sorption (ΔG°), the heat of sorption (ΔH°) and standard entropy (ΔS°) changes during the sorption process were calculated using eqns. 11 and 12 on a temperature range of 25-40 °C at initial concentration 50 mg/L of Cr⁶⁺ ions and dose 4 g/L for activated carbon and bentonite. The values of ΔH° and ΔS° (Table-5) were obtained from the slope and intercept of a plot of ln K_c versus 1/T (Fig. 11).

36.72

0.1268

Bentonite



Fig. 11. Plot of ln K_c versus 1/T for Cr⁶⁺ ions adsorption onto activated carbon and bentonite for 50 mg/L initial concentration at constant adsorbents dose: 4 g/L

The negative values of ΔG° indicate the spontaneous nature of the process and more negative value with increase of temperature showed that an increased in temperature favours the sorption process. The positive values of ΔH° indicated that the sorption process was endothermic in nature and the positive values of ΔS° showed the increased randomness at solid/solution interfaces during the adsorption of metal ions onto both adsorbents and also reflected the affinity of activated carbon and bentonite toward Cr⁺⁶ ions under consideration. It is also suggested that the positive values of entropy indicated some structural changes in the adsorbate and adsorbent⁴⁰⁻⁴².

Conclusion

Both adsorbents can be successfully used for removing of chromium(VI) ions from wastewater. The maximum adsorption percentages of Cr(VI) ions using both adsorbents were achieved within 2 h. The adsorption percentages of Cr^{6+} ions increased sharply by increasing adsorbent dose. As the initial concentration of ions increased the percentage removal using activated carbon and bentonite decreased. The best temperature for the maximum adsorption is found to be 30-40 °C for activated carbon, while the adsorption using bentonite is less affected by increasing temperature. The maximum removals of Cr(VI) ions by both adsorbents were carried out at pH 2. The pseudo-second kinetic order model is suitable for describing

- 2.33

- 2.71

TABLE-4								
LANGMUIR AND FREUNDLICH ISOTHERM CONSTANTS FOR THE ADSORPTION OF Cr6+								
	IONS ONTO ACTIVATED CARBON AND BENTONITE AT 25 °C							
Adapthant	Lar	Langmuir isotherm constants			Freundlich isotherm constants			
Ausorbent	$q_{max}(mg/g)$	b (L/mol)	\mathbb{R}^2	K_{f} (mg/g)	n	\mathbb{R}^2		
Activated carbon	38.17	0.0252	0.9686	1.8446	2.26	0.9953		
Bentonite	48.83	0.0377	0.9658	1.5826	1.78	0.9995		
TABLE-5								
THERMODYNAMIC PARAMETERS FOR THE ADSORPTION OF Cr(VI) IONS ONTO ACTIVATED CARBON AND BENTONITE								
Adsorbent	ΔH° (kj mol ⁻¹) ΔS	$\Lambda S^{\circ}(ki \text{ mol}^{-1}K^{-1})$	$\Delta G^{o}(kj mol^{-1})$					
Ausorbent		$\Delta S(K) mor(K) =$	25 °C	30°C	35°C	40 °C		
Activated carbon	51.45	0.1776	- 1.24	- 2.12	- 3.00	- 3.89		

- 1.06

- 1.70

the adsorption system. The obtained experimental data has been well described by Langmuir and Freundlich isotherm models into both activated carbon and bentonite.

Different thermodynamic parameters, viz., ΔH° , ΔS° and ΔG° have also been evaluated and it has been found that the sorption was feasible, spontaneous and endothermic in nature. The positive value of the entropy change, suggested the increased randomness.

REFERENCES

- N.R. Jyothi, N.A.M. Farook, M.Y. Cho and J. Shim, *Asian J. Chem.*, 23, 4125 (2013).
- 2. S.K. Ouki and R.D. Neufeld, J. Chem. Technol. Biotechnol., 70, 3 (1997).
- 3. H.S. Altundogan, Process Biochem., 40, 1443 (2005).
- J.F. Papp, US Geological Survey (USGS) Mineral commodity summaries, In eds.: Guertin *et al.*, Chromium(VI) Handbook, CRC Press, p. 2005 (2003); http://minerals.er.U.S.G.S.gov/minerals/pubs/commodity/chromium/.
- G. Rojas, J. Silva, J. A. Flores, A. Rodriguez and M. L'Maldonado, Sep. Purif. Technol., 44, 31 (2005).
- B.J. Alloway, Heavy Metals in Soils, Blackie Academic and Professional, London, edn. 2, p. 368 (1995).
- 7. I. Dupont and E. Guillon, *Environ. Sci. Technol.*, **37**, 4235 (2003).
- US, Department of Health and Human Services, Toxicological Profile for Chromium, Public Health Services Agency for Toxic Substances and Diseases Registry, Washington, DC (1991).
- 9. M. Cieslak-Golonka, Polyhedron, 15, 3667 (1995).
- 10. T. Norseth, Environ. Health Perspectives, 40, 121 (1981).
- 11. C.R. Myers, J.M. Myers, B.P. Carstens and W.E. Antholine, *Toxic Subst. Mechan.*, **19**, 25 (2000).
- 12. A. Zhitkovich, G. Quievryn, J. Messer, Z. Motylevich, *Metal Toxicity*, **110**, 729 (2002).
- 13. Z. Kowalski, J. Hazard. Mater., 37, 137 (1994).
- 14. I.B. Singh and D.R. Singh, Environ. Technol., 23, 85 (2002).
- 15. F.N. Acar and E. Malkoc, Bioresour. Technol., 94, 13 (2004).
- 16. Bureau of Indian Standards, IS: 10500-1991.
- J.W. Patterson, Wastewater Treatment Technology, Ann Arbor Science Publishers, Inc., New York, USA (1977).
- G. Tiravanti, D. Petrluzzelli and R. Passino, *Water Sci. Technol.*, 36, 197 (1997).

- S. Dahbi, M. Azzi and M. de la Guardia, *Fresenius J. Anal. Chem.*, 363, 404 (1999).
- C.C. George, Electroplating Wastewater Pollution Control Technology, Noyes Publications, Park Ridge, pp. 30-39 (1985).
- 21. M. Valix, W.H. Cheung and K. Zhang, J. Hazard. Mater., B135, 395 (2006).
- 22. S.H. Lin and R.S. Juang, J. Hazard. Mater., 92, 315 (2002).
- 23. S.C. Tsai, S. Ouyang and C.N. Hsu, Appl. Radiat. Isot., 54, 209 (2001).
- M.H. Al-Qunaibit, W.K. Mekhemer and A.A. Zaghloul, *J. Colloid Interf. Sci.*, **283**, 316 (2005).
- Y.B. Zhan, A. Shukla, S. Shukls and K.L. Dorris, J. Hazard. Mater., 80, 33 (2000).
- C. Namasivayam, K. Kadirvelu and M. Kumuthu, *Bioresour. Technol.*, 64, 77 (1998).
- U.K. Garg, M.P. Kaur, V.K. Garg and D. Sud, *Hazard. Mater.*, 140, 60 (2007).
- K. Mohanty, M. Jha, B.C. Meikap and M.N. Biwas, *Chem. Eng. J.*, 117, 71 (2006).
- T. Karthikeyan, S. Rajgopal and L.R. Miranda, J. Hazard. Mater., B124, 192 (2005).
- Anon, Standard Methods for the Examination of Water and Wastewater, Washington, DC, USA, edn. 19 (1995).
- 31. D.C. Sharma and C.F. Forster, Bioresour. Technol., 49, 31 (1994).
- 32. S. Babel and T.A. Kurniawan, J. Hazard. Mater., B97, 219 (2003).
- V.J. Inglezakis, M.D. Loizidou and H.P. Grigoropoulou, J. Colloid Interf. Sci., 275, 570 (2004).
- 34. (a) P.A. Domenico and F.W. Schwartz, Physical and Chemical Hydrogeology, John Wiley and Sons, New York, edn. 1 (1990); (b) L.N. Reddi and H.I. Inyang, Geo-Environmental Engineering Principles and Applications, Marcel Decker Inc. New York (2001); (c) O. Nitzsche and H. Vereecken, *Mine Water Environ.*, 21, 15 (2002).
- S. Ricordel, S. Taha, I. Cisse and G. Dorange, *Sep. Purif. Technol.*, 24, 389 (2001).
- 36. I. Uzun and F. Guzel, Turk. J. Chem., 24, 291 (2000).
- 37. S. Lagergren, Handlingar, 24, 1 (1898).
- 38. Y.S. Ho and G. Mckay, Process Biochem., 34, 451 (1999).
- 39. J. Zeldowitsch, Acta Physiochim. URSS, 1, 364 (1934).
- H.S. Altundogan, S. Altundogan, F. Tumen and M. Bildik, Waste Mange., 20, 761 (2000).
- 41. H.G. Fuhrman, J.C. Tjell and D. Mcconchie, *Environ. Sci. Technol.*, **38**, 2428 (2004).
- M. Ajmal, R.A.K. Rao, S. Anwar, J. Ahmed and R. Ahmed, *Bioresour*. *Technol.*, 86, 147 (2003).